




An Efficient Representation for Irradiance Environment Maps Ravi Ramamoorthi Pat Hanrahan Stanford University












Assumptions

- · Diffuse surfaces
- Distant illumination
- No shadowing, interreflection

Hence, Irradiance is a function of surface normal



Previous Work

- Precomputed (prefiltered) Irradiance maps [Miller and Hoffman 84, Greene 86, Cabral et al 87]
- Irradiance volumes [Greger et al 98]
- Global illumination [Wilkie et al 00]

Empirical: Irradiance varies slowly with surface normal

- Low resolution Irradiance maps
- Irradiance gradients [Ward 92]

New Theoretical Results

Analytic Irradiance Formula

[Ramamoorthi Hanrahan 01, Basri Jacobs 01]

- Expand Radiance, Irradiance in basis functions
- Analytic formula for Irradiance coefficients

Key Results

- Irradiance approx. for all normals using 9 numbers
- Can be computed as quadratic polynomial

Contributions

- Theory: frequency domain analysis
- Efficient computation of Irradiance
- Procedural rendering algorithm (no textures)
- New representation: apply to lighting design

Computing Irradiance

• Classically, hemispherical integral for each pixel


Incident Radiance








Irradiance


- Lambertian surface is like low pass filter
- · Frequency-space analysis














Computing Light Coefficients


Compute 9 lighting coefficients L_{lm}

- 9 numbers instead of integrals for every pixel
- Lighting coefficients are moments of lighting

$$L_{lm} = \int_{\boldsymbol{q}=0}^{\boldsymbol{p}} \int_{\boldsymbol{f}=0}^{2\boldsymbol{p}} L(\boldsymbol{q}, \boldsymbol{f}) Y_{lm}(\boldsymbol{q}, \boldsymbol{f}) \sin \boldsymbol{q} \, d\boldsymbol{q} d\boldsymbol{f}$$

· Weighted sum of pixels in the environment map

$$L_{lm} = \sum_{pixels(\boldsymbol{q},\boldsymbol{f})} envmap[pixel] \times basisfunc_{lm}[pixel]$$



Rendering

Irradiance approximated by quadratic polynomial

$$\begin{split} E(n) &= c_4 L_{00} 1 + 2 c_2 L_{11} x + 2 c_2 L_{1-1} y + 2 c_2 L_{10} z + c_5 L_{20} (3 z^2 - 1) + \\ & 2 c_1 L_{2-2} x y + 2 c_1 L_{21} x z + 2 c_1 L_{2-1} y z + c_1 L_{22} (x^2 - y^2) \end{split}$$

$$E(n) = n^t M n$$

(depends linearly on coefficients L_{lm}) Surface Normal vector column 4-vector


Hardware Implementation

$$E(n) = n^t M n$$

Simple procedural rendering method (no textures)

- Requires only matrix-vector multiply and dot-product
 In software or NVIDIA vertex programming hardware

surface float1 irradmat (matrix4 M, float3 v) { float4 $n = \{v, 1\}$; return dot(n, M*n);



Lighting Design Final image sum of 3D basis functions scaled by L_{lm} Alter appearance by changing weights of basis functions



Summary

Theory

- · Analytic formula for irradiance
- Frequency-space: Spherical Harmonics
- To order 2, constant, linear, quadratic polynomials
- 9 coefficients (up to order 2) suffice

Practical Applications

- Efficient computation of irradiance
- Simple procedural rendering
- New representation, many applications

Implications and Future Work

- 9 parameter model important in other areas
- Inverse Rendering (Wednesday) [SIGGRAPH 01]
 - Lighting variability object recognition [CVPR 01]

Frequency space for rendering

- Environment maps with general BRDFs?
- Applications to offline rendering?

http://graphics.stanford.edu/papers/envmap/ Source code, examples, links to theory paper,...

Acknowledgements

- Stanford Real-Time Programmable Shading System
 - · Kekoa Proudfoot, Bill Mark
- Readers of early drafts
 - Bill Mark, Kekoa Proudfoot, Sean Anderson, David Koller, Ron Dror, anonymous reviewers
- Models
 - · Armadillo: Venkat Krishnamurthy
 - · Light probes: Paul Debevec
- Funding
 - Hodgson-Reed Stanford Graduate Fellowship
 - NSF ITR #0085864 "Interacting with the Visual World"

The End

Compare to Point Sources Irradiance Map Texture Quadratic Polynomial 6 Directional Light sources Note Mach Banding